

Your **SIMPLE** Battery fit **ALL**

SIMPO

HV

Robustness
Residential Storage
6.4kWh~230.4kWh

 **6.4kWh~28.8kWh per Tower**
2~9 Batteries each Tower



Proven LFP Prismatic Cell

Prismatic LFP- Over **10GWh** Tracking
Record Reliability proved with Millions
ESS installations



One Fits All

Up to **8 Towers** in Parallel
230.4kWh from Residential to
Commercial



Life Time Extension

Allow Extension any Time in Product Life
No Adjust to Same SOC Necessary



One Person Installation

No Screwing Simple Installation



Automatic Configuration

No Laptop **1 Click to Run**
No App Configuration Needed

**Secure Your Storage Bonus Now
with Kostal PLENTICOIN**



KOSTAL

www.zyc.energy



DACH Center (DE/EN)
+49 771 99871998



EU Center (EN/ES/FR)
+34 697919475
+31 6 020 700 00

**Your Support
Always Nearby**



Minimum Configuration
for Entry-level Storage



6.4kWh



28.8kWh
9 * 3.2kWh



230.4kWh
8 * 28.8kWh

Specification of SIMPO HV

Module Data	3.2kWh, 64V, 36kg							
Module Quantity In Tower	2	3	4	5	6	7	8	9
Usable Energy(kWh)	6.4	9.6	12.8	16	19.2	22.4	25.6	28.8
Nominal Voltage(V)	128	192	256	320	384	448	512	576
Max Continuous Current(A)	30							
Peak Output Current(A)	45, 5s							
Weight(Kg)	92.8	129	166	202	238	275	311	348
Dimension W(mm)	610							
Dimension D(mm)	240							
Dimension H(mm)	670	860	1050	1240	1430	1620	1810	2000
Round-trip Efficiency	≥ 96.0%							
Charging Temp Range(°C)	-10~55							
Discharging Temp Range(°C)	-20~55							
Operating Humidity	Up to 95% (Non-condensing)							
IP Rating	IP65							
Communication	CAN / Modbus RS485							
Altitude(m)	≤ 3000							
Warranty	10 Years							
Scalability(Parallel)	1-8 Towers							
Certificate	UN38.3 / CE / IEC62619 / CEC / VDE2510-50 / IEC62040 / IEC62477							